

STRIKER 400

Thyristor based welding power source, suitable for MIG/MAG Semiautomatic and Automatic welding applications



- Light weight, Compact design of Power source, Wire feeder and Torch
- Crater Voltage and Current control possible with ON/OFF switch
- LED Indications for Mains ON and Trip signal
- Globule Detachment Technique keeps the tip ready without globule formation for next welding cycle
- Protection against overheating and very high secondary short circuit current
- Flux core or solid wire selection switch and Gas check Toggle switch on front panel
- Special construction of transformer – resulting in faster response time and Excellent Arc dynamics
- Digital voltage and current meters on front panel
- Wheels for easy movement of machine on the shop floor

DETAILS OF COMPLETE SYSTEM:

The complete system consists of power source, wire feeder, interconnecting cables and Torch as option. Remote control is provided along with the outfit to enable the user to set voltage and current while welding.



WELDERS TO THE NATION SINCE 1951
ADOR WELDING LIMITED

(Formerly Known as Advani-Oerlikon Ltd.)

www.adorwelding.com



STRIKER 400



TECHNICAL SPECIFICATIONS	UNIT	TCVR 405 (STRIKER 400)	
INPUT			
VOLTAGE	VOLTS, AC	415 , +10%, -10%	
PHASE	NO.	3	
FREQUENCY	HZ	50	
INPUT KVA	KVA	18.7 @ 100% DUTY CYCLE, 23 @ 60% DUTY CYCLE	
RATED INPUT CURRENT (MAX.)	AMPS, AC	32	
OUTPUT			
OPEN CIRCUIT VOLTAGE	VOLTS, DC	55 V	
WELDING CURRENT RANGE	AMPS, DC	50 - 400	
WELDING CURRENT @ 100% DUTY CYCLE	AMPS, DC	310	
WELDING CURRENT @ 60% DUTY CYCLE		400	
WELDING VOLTAGE RANGE	VOLTS, DC	16 - 39	
GENERAL			
INGRESS PROTECTION	CLASS	IP23	
COOLING	TYPE	FORCED AIR	
INSULATION	CLASS	H	
DIMENSIONS (L X W X H)	MM	780 X 450 X 915	
WEIGHT	KG	157	
WIRE FEEDER	UNIT	FEEDLITE 20 ST	FEEDLITE 40 ST
DRIVE UNIT	TYPE	2 ROLL PRINT MOTOR	4 ROLL PRINT MOTOR
MOTOR VOLTAGE	VOLTS, DC	18.3	18.3
WIRE SPEED	METERS PER MINUTE	1.5 - 18	1.5 - 18
WIRE SPOOL CAPACITY	KG	15	15
SUITABLE FOR WIRE DIAMETER	MM	0.8, 1.0, 1.2 AND 1.6	0.8, 1.0, 1.2 AND 1.6
INCH SWITCH		ON WIRE FEEDER	ON WIRE FEEDER
DIMENSIONS (L X W X H)	MM	530 X 230 X 315	530 X 230 X 315
WEIGHT	KG	9	9

- Warranty: One year from the date of purchase. ADOR WELDING LIMITED warrants that all new equipment sold from Plant/Area Offices / Authorized Distributors are free from defects in materials and workmanship and will perform in full accordance with applicable specifications.
- In view of continuous development, ADOR WELDING LIMITED reserves the right to modify/change the design and /or the specifications without any prior notice.
- Backed by dedicated customer care package.



WELDERS TO THE NATION SINCE 1951
ADOR WELDING LIMITED

(Formerly Known as Advani-Oerlikon Ltd.)

www.adorwelding.com



Corporate Marketing Office: Survey No. 147 / 2B +3, Near Akurdi Chowk,
 Chinchwad, Pune – 411019. Maharashtra, INDIA.
 Tel.: +91 20 4070 6000, Fax: +91 20 4070 6001, Email: cmo@adorians.com